

3MXF52A9

Cooling (50Hz 230V)

Outdoor unit	Indoor unit	Cooling capacity [kW]			Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room A	Room B	Room C	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	
3MXF52A2V1B 3MXF52A2V1B9	2.0	2.00	---	---	1.60	2.00	3.00	0.36	0.57	0.88	1.60	2.57	3.96	96
	2.5	2.50	---	---	1.60	2.50	3.20	0.36	0.76	0.98	1.62	3.43	4.41	96
	3.5	3.50	---	---	1.60	3.50	4.20	0.37	1.16	1.48	1.63	5.27	6.69	96
	2.0+2.0	2.00	2.00	---	1.70	4.00	6.00	0.35	1.01	2.64	1.55	4.58	11.95	96
	2.0+2.5	2.00	2.50	---	1.70	4.50	6.20	0.35	1.13	2.53	1.55	5.12	11.43	96
	2.0+3.5	1.89	3.31	---	1.70	5.20	6.30	0.35	1.31	2.64	1.55	5.92	11.95	96
	2.5+2.5	2.50	2.50	---	1.70	5.00	6.30	0.35	1.24	2.68	1.55	5.60	12.13	96
	2.5+3.5	2.17	3.03	---	1.70	5.20	6.30	0.35	1.29	2.61	1.55	5.87	11.77	96
	3.5+3.5	2.60	2.60	---	1.70	5.20	6.40	0.35	1.28	2.61	1.55	5.81	11.81	96
	2.0+2.0+2.0	1.73	1.73	1.73	1.80	5.20	7.00	0.37	1.27	2.54	1.65	5.76	11.48	96
	2.0+2.0+2.5	1.60	2.00	2.00	1.80	5.20	7.00	0.37	1.26	2.53	1.65	5.71	11.43	96
	2.0+2.0+3.5	1.39	1.39	2.43	1.90	5.20	7.20	0.39	1.25	2.49	1.75	5.65	11.24	96
	2.0+2.5+2.5	1.49	1.86	1.86	1.80	5.20	7.10	0.39	1.25	2.43	1.75	5.65	11.00	96
	2.0+2.5+3.5	1.30	1.63	2.28	1.90	5.20	7.20	0.39	1.24	2.46	1.75	5.60	11.10	96
	2.0+3.5+3.5	1.16	2.02	2.02	1.90	5.20	7.30	0.39	1.24	2.46	1.75	5.60	11.10	96
	2.5+2.5+2.5	1.73	1.73	1.73	1.90	5.20	7.10	0.39	1.24	2.51	1.75	5.60	11.34	96
	2.5+2.5+3.5	1.53	1.53	2.14	1.90	5.20	7.20	0.39	1.24	2.47	1.75	5.60	11.15	96

Heating (50Hz 230V)

Outdoor unit	Indoor unit	Heating capacity [kW]			Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room A	Room B	Room C	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	
3MXF52A2V1B 3MXF52A2V1B9	2.0	2.70	---	---	1.10	2.70	3.80	0.30	0.95	1.37	1.34	4.25	6.20	96
	2.5	3.40	---	---	1.10	3.40	4.20	0.30	1.26	1.46	1.34	5.67	6.61	96
	3.5	4.20	---	---	1.10	4.20	4.80	0.30	1.77	1.88	1.34	7.99	8.51	96
	2.0+2.0	3.40	3.40	---	1.20	6.80	7.00	0.32	1.99	2.45	1.44	9.00	11.10	96
	2.0+2.5	3.02	3.78	---	1.20	6.80	7.00	0.32	1.97	2.44	1.44	8.95	11.05	96
	2.0+3.5	2.47	4.33	---	1.20	6.80	7.10	0.32	1.96	2.45	1.44	8.89	11.10	96
	2.5+2.5	3.40	3.40	---	1.20	6.80	7.00	0.32	1.91	2.41	1.44	8.66	10.91	96
	2.5+3.5	2.83	3.97	---	1.30	6.80	7.20	0.32	1.91	2.55	1.44	8.66	11.55	96
	3.5+3.5	3.40	3.40	---	1.40	6.80	7.30	0.32	1.90	2.58	1.44	8.61	11.68	96
	2.0+2.0+2.0	2.27	2.27	2.27	1.30	6.80	8.00	0.32	1.73	2.31	1.44	7.84	10.46	96
	2.0+2.0+2.5	2.09	2.09	2.62	1.30	6.80	8.00	0.32	1.72	2.28	1.44	7.81	10.33	96
	2.0+2.0+3.5	1.81	1.81	3.17	1.40	6.80	8.10	0.32	1.71	2.29	1.44	7.76	10.37	96
	2.0+2.5+2.5	1.94	2.43	2.43	1.30	6.80	8.00	0.32	1.71	2.26	1.44	7.76	10.24	96
	2.0+2.5+3.5	1.70	2.13	2.98	1.50	6.80	8.10	0.32	1.70	2.28	1.44	7.70	10.33	96
	2.0+3.5+3.5	1.51	2.64	2.64	1.50	6.80	8.20	0.32	1.69	2.33	1.44	7.64	10.55	96
	2.5+2.5+2.5	2.27	2.27	2.27	1.40	6.80	8.00	0.32	1.70	2.24	1.44	7.70	10.14	96
	2.5+2.5+3.5	2.00	2.00	2.80	1.50	6.80	8.10	0.32	1.69	2.26	1.44	7.64	10.24	96

Notes

- The total capacity of each connected indoor unit is up to 8.5-kW.
- The values above are for connecting with the following indoor unit types:
-2.0, 2.5, 3.5- kW class
Wall-mounted -FTXF-A, FTXF-B- series
- These indoor units can only be used in a multi-unit setup.
- Cooling capacity conditions
Indoor temperature :27°C DB / :19°C WB
Outdoor temperature :35°C DB
- Heating capacity conditions
Indoor temperature :20°C DB
Outdoor temperature :7°C DB / :6°C WB